

# MT-2001 Video Controller



### Video controller with built-in memory

MT-2001 is the ideal video controller to control the built-in TBC and video processor equipped in the broadcast and professional VTRs. The controller allows maximum of 4 VTRs to be controlled and save the settings into the memory.

Various type of VTR formats such as HD / D1 / D2 / Analog control parameter are supported and can be combined in a single chassis.

## MT-2001 Video Controller

#### **Key Features**

- □ Support HD formats VTR
- □ Support maximum of 4 VTRs by switching
- □ Support 100 registry settings per port
- Optional board to support and combine with various VTR format
- □ Support HD / D1 / D2 / Analog VTR control parameters
- □ Support loading of unity (Center) setting
- Compact size (EIA 1U with 110mm depth)

Port No. (Slot)	4 Ports				
Memory number	100 registry per port				
Adjust parameter	HD Mode	D1 Mode	D2 Mode	Analog Mode	
	MASTER		VIDEO		
* Depending on the	γ		CHROMA		
type of connected	Pb	B-Y	HUE		
VTR, the operation	Pr	R-Y	SET UP		
conditions are different	SET UP		V. PHASE	Y/C DELAY	
	SYNC. PHASE		H. PHASE		
	FINE		SC PHASE		
Optional board	MT-20S422			MT-20A25V/50V	
Power	AC100-240V 50/60Hz				
Power Consumption	Approx 20W (Max)				
Dimension (W x H x D)	430 x 44 x 110 mm (Exclude uneven surface)				
Weight	Approx 2Kg				
Extension Port	1 port (HR12 Series) * Use during maintenance (Not use in normal operation)				
Accessories	Rack ear x 1 pair, User Manual x 1 set				



### Option

Expansion board (Optional)					
	MT-20S422	MT-20A50V	MT-20A25V		
	Serial communication control interface	5V Analog voltage control interface	2.5V Analog voltage control interface		
Connector	D-Sub 9P (Female socket)	D-Sub 15P (Female socket)	D-Sub 15P (Female socket)		
Mainly supported VTR	HDCam / D2 / DVCPRO HD / HD-D5 etc	HDCam / Betacam etc	DVCPRO / MII etc		
Connection cable (Optional)					
	SDC09-5/10 MT-20S422 connection cable				
	(DB9Male - DB9Male) 5m / 10m	SAC-5/10 MT-20A50V connection cable	MAC-5/10 MT-20A25V connection cable		
	SDC15-5/10 MT-20S422 connection cable	(DB15Male - DB15Female) 5 / 10m	(DB15Male - DB15Male) 5 / 10m		
	(DB9Male - DB15Male) 5m / 10m				
* The compatibility of VTR and controllable parameter may be different, please consult our sales or technical department for more details about optional interfaces and connection cables.					

Specifications and designs subject to change without notice.

#### Manufacturer



MUSASHI CO., LTD.

NK Fuji Bldg., 3/F., 3-21-1, Shimo-Ochiai, Shinjuku-ku, Tokyo, 161-0033, Japan Tel : +81-3-5996-7455 Fax : +81-3-5996-7484 http : //www.musashi-kk.co.jp email : info@musashi-kk.co.jp Dealer